



- 1 Supports
- 2 Carriers
  - Pin/bolt system
  - Hole patterns
- 3 Supports
  - To secure roof
  - Can be used to attach C-LUX lights (see catalogue section 7)
- 4 Roof
  - To protect control units from environment influences
- 5 Brackets
  - transport eyes
  - For wall mounting (possible on top and bottom)
- 6 Fixing brackets
  - for side wall fixing
- 7 Earth tag
- 8 Angle brackets
  - Free-standing
  - Can be fixed to the floor

### Technical Data

Version	8298/01-061	8298/01-062	8298/01-051	8298/01-052
Enclosures	8146	8146	8125	8125
Material	Sheet steel, galvanised	Stainless steel 1.4301	Sheet steel, galvanised	Stainless steel 1.4301
Carriers, supports	U-beam 2,5 mm thick	U-beam 2,5 mm thick	U-beam 2,5 mm thick	U-beam 2,5 mm thick
Roof	Shaped sheet metal 1,5 mm thick	Shaped sheet metal 1,5 mm thick	Shaped sheet metal 1,5 mm thick	Shaped sheet metal 1,5 mm thick
Angle brackets	Shaped sheet metal 2,5 mm thick	Shaped sheet metal 2,5 mm thick	Shaped sheet metal 2,5 mm thick	Shaped sheet metal 2,5 mm thick
Fixing brackets	Shaped sheet metal 4 mm thick	Shaped sheet metal 4 mm thick	Shaped sheet metal 4 mm thick	Shaped sheet metal 4 mm thick