

## Installation Material and Accessories


### Cable Glands Made of Metal with Strain Relief Series HSK-MZ



09908E00

#### Cable Glands Made of Metal with Strain Relief Series HSK-MZ

- Version EEx e II
- IP68
- Can be used in
  - Zone 1 and Zone 2
  - Zone 21 and Zone 22
- Usable for portable equipment
- For flexible connecting cable



09906E00

#### Selection Table

Thread AG	Cable dia. range [mm]	Dimensions [mm]			Order number	Weight kg
		H	SW	GL		
M 16 x 1.5	4 - 8	29	19	6	<b>106081</b>	0.028
M 16 x 1.5	5 - 10	30	20	6	<b>106082</b>	0.028
M 20 x 1.5	7 - 12	33	22	6	<b>106083</b>	0.043
M 20 x 1.5	10 - 14	33	24	6	<b>106084</b>	0.051
M 25 x 1.5	14 - 18	37	30	7	<b>106085</b>	0.082
M 32 x 1.5	20 - 25	43	40	8	<b>106086</b>	0.152
M 40 x 1.5	24 - 32	50	50	8	<b>106087</b>	0.242
M 50 x 1.5	32 - 38	51	57	9	<b>106088</b>	0.560
M 63 x 1.5	37 - 44	52	64/68	10	<b>106089</b>	0.616

#### Technical Data

Explosion protection	II 2 GD EEx e II
Certificates	KEMA 99 ATEX 6971 X
Material	
Cable gland	Brass nickel-plated
Formed seal	NBR
O-ring	NBR
Terminal protection	Polyamide
Type of Protection	IP68 - 10 bar (in specified terminal area)
Ambient conditions	- 60 ... + 105 °C

We reserve the right to make alterations to the technical data, weights, dimensions, designs and products available without notice. The illustrations cannot be considered binding.